## 2025 FORD BRONCO® SPORT

## TECHNICAL SPECIFICATIONS



## **BODY**

| RODA                       |  |  |
|----------------------------|--|--|
| Body type                  | 5-door, 5-passenger sport utility vehicle  |  |
| Construction               | Unibody  |  |
| Standard trim levels (std) | Big Bend™/Outer Banks™/Badlands™/Heritage/Free Wheeling™   |  |
| Optional packages (opt)    | Outer Banks Sasquatch Package/Badlands Sasquatch Package   |  |
| Final assembly location    | Hermosillo Stamping & Assembly Plant, Hermosillo, Mexico   |  |
| POWERTRAIN                 | Big Bend, Outer Banks, Heritage, Free Wheeling (std)/Outer Banks Sasquatch Package (opt)   | Badlands (std)/Badlands Sasquatch<br>Package (opt)   |
| Engine                     | 1.5L EcoBoost® with Auto-Start Technology  | 2.0L EcoBoost with Auto Start-Stop Technology  |
| Configuration              | Aluminum block and head, In-line 3 cylinder  | Aluminum block and head, In-line 4 cylinder  |
| Manufacturing location     | CHEP Mexico  | Dearborn Engine  |
| Intake manifold            | Composite  | Composite  |
| Exhaust manifold           | Integrated   | Integrated   |
| Valvetrain                 | DOHC, Ti-VCT   | DOHC, Ti-VCT   |
| Pistons                    | Aluminum   | Aluminum   |
| Connecting rods            | Powder Forged  | Powder Forged  |
| Bore x stroke              | 3.31-in. x 3.54-in.  | 3.31-in. x 3.54-in.  |
| Displacement               | 91.4 cu. in./1,497 cc  | 121.7 cu. in./1,995 cc   |
| Compression ratio          | 11.0:1   | 10.8:1   |
| Engine control system      | PCM  | PCM  |
| Crankshaft                 | Cast Iron  | Forged Steel   |
| Horsepower <sup>1</sup>    | 180*   | 238*   |
| Torque (lbft.)¹            | 200 lbft.*   | 277 lbft.*   |
| Recommended fuel           | 87-octane (min.)   | 87-octane (min.)/91+ (rec.)  |
| Fuel delivery              | GTDI   | GTDI and PFI   |
| Fuel capacity              | 15.7 gallons   | 15.7 gallons   |
| Oil capacity (with filter) | 5 quarts   | 6.1 quarts   |
| Coolant capacity           | 7.5 quarts   | 8.5 quarts   |
| Fuel economy (target)3     | TBD  | TBD  |
| DRIVETRAIN                 |  |  |
| Layout                     | 4X4 system with Air cooled PTU,<br>disconnectable driveshaft and single clutch<br>RDU/Sasquatch includes 4WD lock and dual<br>clutch RDU with Diff Lock Capability | 4X4 system with water cooled PTU,<br>disconnectable driveshaft with 4WD Lock,<br>and dual clutch RDU with Diff Lock Capability |
| TRANSMISSION               |  |  |
| Tyne                       | R-sneed automatic  | 8-speed automatic SelectShift with oil cooler  |



Type

<sup>1</sup>Horsepower and torque ratings based on premium fuel per SAE J1349® standard. <sup>2</sup>Available November 2024 (MP2). Your results may vary. For editorial use only. Information correct at time of publication. Check media.ford.com for updates.

8-speed automatic



and manual shifting mode with standard

paddle shifters

| G.O.A.T. MODES™ TERRAIN<br>MANAGEMENT SYSTEM | Big Bend, Outer Banks, Heritage, Free Wheeling (std)/Outer Banks Sasquatch Package (opt)   | Badlands (std)/Badlands Sasquatch<br>Package (opt)   |
|--|--|--|
| Selectable drive modes                       | Normal, ECO, Sport, Slippery, Off-Road   | Normal, ECO, Sport, Slippery, Off-Road, Rally,<br>Rock Crawl   |
| GEAR RATIOS                                  |  |  |
| First  | 4.69   | 4.69   |
| Second                                       | 3.31   | 3.31   |
| Third  | 3.01   | 3.01   |
| Fourth                                       | 1.92   | 1.92   |
| Fifth  | 1.45   | 1.45   |
| Sixth  | 1  | 1  |
| Seventh                                      | 0.75   | 0.75   |
| Eighth                                       | 0.62   | 0.62   |
| Final gear ratio                             | 3.81   | 3.81   |
| Reverse                                      | -2.96  | -2.96  |
| BRAKES                                       |  |  |
| Front brakes                                 | 308 mm x 27 mm vented rotors, single-piston calipers with ABS  | 308mm x 27mm vented disc brakes, single-<br>piston calipers with ABS. 0.5mm thicker braking<br>plates for improved heat dissipation  |
| Rear brakes                                  | 302mm x 11mm disc brakes, single-piston calipers with ABS and electric park functionality  | 302mm x 11mm disc brakes, single-piston calipers with ABS and electric park functionality  |
| Brake booster type                           | Electric   | Electric   |
| WHEELS & TIRES                               |  |  |
| Wheels                                       | 17x7; 18x7 (std only)  | 17x7   |
| Tires  | 225/65 R17 AS Continental (std Big Bend)/<br>235/65 R17 AT Goodyear (opt for Outer Banks)  | 225/65/R17 AT Continental (std)<br>235/65/R17 AT Goodyear(opt)   |
|  | 225/60 R18 AS Michelin (std Outer Banks)   |  |
|  | 225/65 R17 AT Continental (opt Big Bend)   |  |
| Spare  | Tire Mobility Kit (std); Full-size spare (opt)   | Full-size spare  |
| CHASSIS                                      |  | ·  |
| Front suspension                             | Independent MacPherson strut-type with coil spring, stabilizer bar, twin-tube hydraulic gaspressurized dampers; steel subframe with aluminum lower control arm, and cast knuckle | Independent MacPherson strut-type with coil spring, stabilizer bar, twin-tube hydraulic gaspressurized dampers; steel subframe with aluminum lower control arm, and cast knuckle (std); Badlands Sasquatch includes rear Bilstein position-sensitive dampers (PSD) (opt) |
| Rear suspension                              | Independent double lateral link semi-trailing arms with coil spring, stabilizer bar, monotube hydraulic gas-pressurized dampers, and isolated steel subframe                     | Independent double lateral link semi-trailing arms with coil spring, stabilizer bar, monotube hydraulic gas-pressurized dampers, and isolated steel subframe   |
| Front and rear suspension                    | 7.8/9.0 (std)<br>7.9/9.0 (opt)   | 7.9/9.0 (std)<br>8.3/8.7 (opt)   |
| Steering                                     | Electric power-assisted steering (EPAS) with unique tuning for drive modes   | Electric power-assisted steering (EPAS) with unique tuning for drive modes   |



| DIMENSIONS WITHOUT OPTIONS  | Big Bend, Outer Banks, Heritage, Free Wheeling (std)/Outer Banks Sasquatch Package (opt) | Badlands (std)/Badlands Sasquatch<br>Package (opt) |
|---|--|--|
| EXTERIOR (inches unless otherwise noted)                          |  |  |
| Wheelbase   | 105.1  | 105.1  |
| Length  | 173 (std)/175.1 (opt)  | 173.4 (std)/175.1 (opt)                            |
| Nidth, excluding mirrors  | 74.3   | 74.3   |
| Nidth, including mirrors  | 82.2   | 82.2   |
| Width, mirrors folded   | 76.3   | 76.3   |
| Vehicle Height (max.)   | 70.4 (std)/71.7 (opt)  | 71.5 (std)/72.1 (opt)                              |
| rack, front curb  | 63.4 (std)/63.8 (opt)  | 63.8   |
| rack, rear curb   | 62.8 (std)/63.1 (opt)  | 63.1   |
| Front overhang  | 33.7 (std)/35.7 (opt)  | 34 (std)/35.7 (opt)                                |
| Rear overhang   | 34.2 (std)/34.3 (opt)  | 34.3   |
| Approach angle  | 22.1 (std)/24.1 (opt)  | 30 (std)/31.2 (opt)                                |
| Departure angle   | 30.8 (std)/27.3 (opt)  | 26.7 (std)/27.9 (opt)                              |
| Ramp breakover angle, curb  | 18.6 (std)/21 (opt)  | 20.4 (std)/21.7 (opt)                              |
| Minimum running ground clearance                                  | 7.8 (std)/8.8 (opt)  | 8.1 (std)/8.7 (opt)                                |
| Front axle PTU to ground  | 9.5 (std)/10.4 (opt)   | 10.1 (std)/10.6 (opt)                              |
| Rear axle PTU to ground   | 8.8 (std)/10 (opt)   | 9.7 (std)/10.4 (opt)                               |
| NTERIOR (inches unless otherwise noted)                           |  |  |
| Seating capacity  | 5 occupants  | 5 occupants  |
| First-row headroom  | 41.5   | 41.5   |
| irst-row legroom (max.)   | 42.4   | 42.4   |
| irst-row shoulder room  | 57.3   | 57.3   |
| irst-row hip room   | 55.2   | 55.2   |
| Second-row headroom   | 41.7   | 41.7   |
| second-row legroom (max.)   | 36.9   | 36.9   |
| Second-row shoulder room  | 55.6   | 55.6   |
| Second-row hip room   | 53.4   | 53.4   |
| . <b>NEIGHTS AND CAPACITIES</b> (cubic feet unless ot             | herwise noted)   |  |
| otal passenger volume   | 105.6  | 105.6  |
| Cargo volume behind first row (w/o options)                       | 65.2   | 60.6   |
| Cargo vol, behind second row (w/o options)                        | 32.5   | 29.4   |
|   |  |  |
| ADDITIONAL CARGO DIMENSIONS (inches unl                           | ·  | 7.0.4.10.770.74.10                                 |
| ift-in height   | 29.4 (std)/32.2 (opt)  | 31.9 (std)/32.6 (opt)                              |
| Cargo height  | 38.0 (std)/35.3 (opt)  | 35.3 (std)/35.1 (opt)                              |
| Rear opening height   | 32.6 (std)/31.3 (opt)  | 31.3 (std)/31.2 (opt)                              |
| Maximum cargo height  | 38.1 (std)/35.4 (opt)  | 35.4 (std)/35.2 (opt)                              |
| Open liftgate height to ground                                    | 70.7 (std)/72.3 (opt)  | 72.0 (std)/72.7 (opt)                              |
| Cargo length closed – first                                       | 65.0   | 65.0   |
| Cargo length closed – second                                      | 35.6 (std)/34.1 (opt)  | 34.1 (std)/33.7 (opt)                              |
| Cargo length above floor, pehind first row                        | 57.1   | 57.1   |
| Cargo length above floor, pehind second row                       | 24   | 24.0   |
| Compartment width (max.)  | 57.6   | 57.6   |
| Cargo width, wheelhouse   | 41.4   | 41.4   |
| Rear opening width, lower   | 42.6/43.1 (std)/43.1 (opt)   | 43.1   |
| nterior volume – behind first row, first<br>ow passenger volume   | 121.4 cu. ft. (std)/113.4 cu. ft. (opt)  | 116.8 cu. ft. (std)/113.1 cu. ft. (opt)            |
| Interior volume – behind second row, all<br>rows passenger volume | 138.1 cu. ft. (std)/131.7 cu ft. (opt)   | 135.1 cu ft. (std)/131.3 cu. ft. (opt)             |
| /olume, first seat compartment                                    | 56.2 cu. ft. (std)/52.9 cu ft. (opt)   | 56.2 cu. ft. (std)/52.9 cu ft. (opt)               |
| /olume, second seat compartment                                   | 49.4 cu. ft.   | 49.4 cu. ft.                                       |



| TECHNOLOGY                              | Big Bend, Outer Banks, Heritage, Free Wheeling (std)/Outer Banks Sasquatch Package (opt)  | Badlands (std)/Badlands Sasquatch<br>Package (opt)   |
|---|---|--|
|   | Auto High Beam headlamps  | Auto High Beam headlamps   |
|   | BLIS® (Blind Spot Information System) with Cross-Traffic Alert  | BLIS® (Blind Spot Information System) with Cross-Traffic Alert   |
|   | Lane-Keeping System (includes Lane-Keeping<br>Assist, Lane-Keeping Alert and Driver Alert)  | Lane-Keeping System (includes Lane-Keeping<br>Assist, Lane-Keeping Alert and Driver Alert)   |
| Ford Co-Pilot360™ Assist+<br>(standard) | Pre-Collision 1.5 Assist with Automatic Emergency<br>Braking (includes Pedestrian Detection, Forward<br>Collision Warning and Dynamic Brake Support)  | Pre-Collision Assist with Automatic Emergency<br>Braking (includes Pedestrian Detection, Forward<br>Collision Warning and Dynamic Brake Support)   |
|   | Rear View Camera with rear parking sensors  | Rear View Camera with rear parking sensors   |
|   | Adaptive Cruise Control with Stop-and-Go and Lane Centering   | Adaptive Cruise Control with Stop-and-Go and Lane Centering  |
|   | Evasive Steering Assist   | Evasive Steering Assist  |
|   | Rear Cross Traffic Braking  | Rear Cross Traffic Braking   |
| Ford Co-Pilot360 Assist 2.0             | 360-Degree Camera (with split view)   | 360-Degree Camera (with split view)  |
| (optional in Outer Banks,               | Reverse Brake Assist  | Reverse Brake Assist   |
| standard in Badlands)                   | Front Parking Sensors   | Front Parking Sensors  |
| Telematics System                       | 13.2in LCD center screen with SYNC4 (Voice-<br>activated touchscreen navigation system<br>with pinch-to-zoom capability, SiriusXM<br>Traffic and Travel Link®)  | 13.2in LCD center screen with SYNC4 (Voice-activated touchscreen navigation system with pinch-to-zoom capability, SiriusXM Traffic and Travel Link®)   |
|   | 12.3in LCD, fully digital instrument panel  | 12.3in LCD, fully digital instrument panel   |
| Audio System                            | 6 speakers; B&O Sound System by Bang &<br>Olufsen, 10 speakers including subwoofer<br>(available in Outer Banks Tech Package)   | 6 speakers; B&O Sound System by Bang &<br>Olufsen, 10 speakers including subwoofer<br>(available in Badlands Tech Package)   |
|   | Data port USB A and C in front media bin<br>2 x charging ports in Bring Your Own Device bin<br>2 x USB C charging ports in second row   | Data port USB A and C in front media bin<br>2 x charging ports in Bring Your Own Device bin<br>2 x USB C charging ports in second row  |
| Power and Data Ports                    | 12V outlet in front media bin<br>12V outlet in front seat console<br>12V outlet in cargo area<br>Wireless phone charger in front media bin<br>110V/400W power outlet in second row and<br>cargo area (opt Big Bend/Outer Banks) | 12V outlet in front media bin<br>12V outlet in front seat console<br>12V outlet in cargo area<br>Wireless phone charger in front media bin<br>110V/400W power outlet in second row and<br>cargo area |
| Off Road Technology                     | Front camera and 360-degree camera with split view, and unlimited speed in OR modes (opt Outer Banks)   | Front camera and 360-degree camera with split view, and mirror cameras with unlimited speed in OR modes  |
|   | Customizable LCD cluster with Off-road Information screen   | Customizable LCD cluster with Off-road Information screen  |
|   | Trail Control™ w/Trail 1-Pedal Drive (opt)  | Trail Control™ w/Trail 1-Pedal Drive   |



| UX FEATURES                         | Big Bend, Outer Banks, Heritage, Free Wheeling (std)/Outer Banks Sasquatch Package (opt)  | Badlands (std)/Badlands Sasquatch<br>Package (opt)  |
|-------------------------------------|---|---|
| Seating Storage                     | MOLLE straps on first row seatbacks<br>Pouch on first row seatbacks   | MOLLE straps on first row seatbacks<br>Zipper pouch on first row seatbacks<br>Seat side pocket on first row<br>Storage under second row |
| Easy to Clean                       | Cloth seating surface (std on Big Bend)<br>Premium-trimmed (std on Outer Banks)<br>Rubberized cargo floor (opt)<br>Rubberized floor (opt) | Leather-trimmed with mini-perforation seating<br>Rubberized removable second row seatback<br>Rubberized cargo floor<br>Rubberized floor |
|                                     | Liftgate with flip glass  | Liftgate with flip glass  |
|                                     | Roof rails with available cross bars  | Heavy-duty roof rails with tie-down holes and available cross bars  |
|                                     | Cargo tie-downs on cargo floor and carabiner hooks in rear interior trim panels   | Cargo tie-downs on cargo floor and carabiner hooks in rear interior trim panels   |
| Convenience                         | Adjustable flood lights in liftgate   | Adjustable flood lights in liftgate   |
|                                     | Optional cargo management w/foldable table  | Optional cargo management w/foldable table  |
|                                     | Bottle opener located in rear hatch   | Bottle opener located in rear hatch   |
|                                     | Auxiliary Switches in overhead console (opt)  | Auxiliary Switches in overhead console (opt)  |
|                                     | Fender tie-downs (opt)  | Fender tie-downs (opt)  |
| PERFORMANCE                         |   |   |
| Curb weight (lbs)                   | 3,458 (std)/3,729 (opt)   | 3,809 (std)/3,849 (opt)   |
| Payload (lbs)                       | 916 (std)/938 (opt)   | 921 (std)/918 (opt)   |
| Trailer tow (lbs)                   | 2,200   | 2,700   |
| Water fording <sup>3</sup> (inches) | 17.7 (std)/20.6 (opt)   | 23.6  |
| Crawl ratio                         | 18:1  | 18:1  |

